



# vAnalytics™ Account and Port Requirements for On-Premise Deployment

Last Updated: January 20, 2017

Document Version: 1.3



THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS DOCUMENT ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS DOCUMENT ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE ARE PROVIDED "AS IS" WITH ALL FAULTS. VYOPTA DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL VYOPTA BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF VYOPTA HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Other company and product names mentioned herein may be trademarks of their respective companies. Mention of third-party products is for informational purposes only and constitutes neither an endorsement nor a recommendation. Vyopta assumes no responsibility with regard to the performance or use of these products. All understandings, agreements, or warranties, if any, take place directly between the vendors and the prospective users. Every effort has been made to ensure that the information in this document is accurate. Vyopta is not responsible for printing or clerical errors.

Copyright © 2016 Vyopta Incorporated. All rights reserved.

Vyopta® is a registered trademark of Vyopta Incorporated. Reg. USPT



## Vyopta vAnalytics Account and Port Requirements

Infrastructure Type	Account Type	Account Requirements	TCP Port Number	Transport Layer	Traffic Origin	Traffic Destination	Allow Return	Device Notes
<b>Local Video Infrastructure</b>								
Cisco VCS-C / VCS-E Cisco Expressway-E / C	LOCAL	Read-only Admin with API access	443	TCP	vAnalytics Collector	VCS	Yes	All VCS cluster devices must be added.
Cisco TelePresence Server	LOCAL	User with API Access	443 & 22280	TCP	vAnalytics Collector	TP Server	Yes	
Cisco MCU	LOCAL	Administrator Account	443	TCP	vAnalytics Collector	MCU	Yes	If MCU is in a cluster or stacked environment only add Master MCU.
Cisco ISDN Gateway	LOCAL	Administrator Account	443	TCP	vAnalytics Collector	MCU	Yes	
Cisco Unified Communications Manager API	LOCAL	CUCM Application User with Standard CCM Read-only, AXL User Group, and Standard CTI Enabled access	443 & 8443	TCP	vAnalytics Collector	CUCM	Yes	Only CUCM publishers need to be added.
Cisco Unified Communications Manager FTP/SFTP	LOCAL	VYOPTA embedded account	21* or 22 & 2748	TCP	CUCM - Publisher	vAnalytics Collector	Yes	FTP requires that passive FTP be open and allowed from CUCM to the Vyopta data collector. If SFTP is selected then only port 22 must be open. SFTP requires using a third party SFTP client on the Vyopta Data Collector.
Cisco TelePresence Manager TMS & TMSPE	SQL DBA	Read-only DB Account with access to the TMSNG and TMSPE databases (Windows AD login not)	1433*	TCP	vAnalytics Collector	TMS	Yes	1433 is typically the default port. However, large enterprise SQL environments typically requires the SQL DBA to identify the actual port in use.
Cisco TelePresence Content Server API	LOCAL	TMS API Account password for TCS	443	TCP	vAnalytics Collector	TCS	Yes	Must use the API password for the TCS which must be the same password that
Acano - API	LOCAL	User Account with API access	443*	TCP	vAnalytics Collector	Acano Server	Yes	Port 443 is the default port, however the management port is configurable within Acano and maybe a different TCP port such as 445.



## Vyopta vAnalytics Account and Port Requirements Continued

Infrastructure Type	Account Type	Account Requirements	TCP Port Number	Transport Layer	Traffic Origin	Traffic Destination	Allow Return	Device Notes
<b>Local Video Infrastructure</b>								
Acano - CDR Forward	N/A	N/A	22280	TCP	Acano Server	vAnalytics Collector		Acano pushed CDR data to the Vyopta Data Collector on TCP port 22280
Acano Manager	N/A	N/A	5566	TCP	vAnalytics Collector	Acano Manager	Yes	The Vyopta Data Collector can be configured to forward CDR data sent from Acano relaying back to Acano Manager on port 5566 if Acano version is 1.7 or below.
Pexip Infinity Management Node	LOCAL	Admin Account	443	TCP	vAnalytics Collector	Pexip	Yes	Only requires PEXIP Infinity Management Node for Historical and Real Time data collection
Polycom DMA	LOCAL	Admin Account	8443	TCP	vAnalytics Collector	Polycom	Yes	DMA requires Polycom RealPresence Platform API license
Polycom RMX	LOCAL	Admin Account	80 or 443	TCP	vAnalytics Collector	Polycom	Yes	
VidyoPortal - API	LOCAL	Admin Account	443	TCP	vAnalytics Collector	VidyoPortal	Yes	
Vidyo - Database	LOCAL	Admin Account	3306	TCP	vAnalytics Collector	Vidyo	Yes	
WebEx	LOCAL	WebEx Read-only Admin account	443	TCP	vAnalytics Collector	WebEx Address (Local or Cloud Instance)	Yes	
Microsoft Skype for Business	SQL DBA	Read-only DB Account with access to the LcsCDR and QoEMetrics databases (Windows AD login not supported)	1433*	TCP	vAnalytics Collector	Skype for Business	Yes	1433 is typically the default port. However, large enterprise SQL environments typically requires the SQL DBA to identify the actual port in use.